

## HMI DIGITAL 1800 W

HMI DIGITAL | Halogenidové výbojky, jednopaticové



### Druh použití

- Studio
- Stage
- TV

### Výhody produktu

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

### Vlastnosti produktu

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Schopnost horkého restartu



# Technický list výrobku

## Technické údaje

### Parametry

Jmenovitý výkon	1800.00 W
Jmenovité napětí	140 V
Jmenovitý proud	12.9 A
Zápalné napětí Zastudena/zatepla	5/35 kVp

### Fotometrické údaje

Jmenovitý světelný tok	165000 lm
Teplota chromatičnosti	6500 K
Index podání barev Ra	90

### Rozměry & váha

Průměr	40.0 mm
Délka	200.0 mm
Vzdálenost světelného středu	107,0 mm
Mezera mezi elektrodami zastudena	10,0 mm

### Teploty a provozní podmínky

Max. dovolená teplota okolí u patice	450 °C
--------------------------------------	--------

### Životnost

Střední doba života	750 h
---------------------	-------

### Další údaje o produktu

Patice	G38
--------	-----

### Vlastnosti

Chlazení	Convection or forced
Provozní poloha hořáku	Jakýkoli

### Environmental information

<b>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)</b>	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899984202
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

## Technický list výrobku

---

### Bezpečnostní pokyny

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Logistické údaje

Kód výrobku	Popis výrobku	Jednotka balení (kusy/jednotku)	Rozměry (délka x šířka x výška)	Objem	Hrubá hmotnost
4052899984202	HMI DIGITAL 1800 W	Shipping carton box 1	340 mm x 160 mm x 165 mm	8.98 dm <sup>3</sup>	520.00 g

---

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo více samostatných produktů. Při objednávání zadávejte jednotky balení nebo násobky jednotek balení.

---

### Vyloučení odpovědnosti

Změny bez předchozího upozornění vyhrazeny. Chyby a opomenutí vyhrazeny. Vždy se ujistěte, že používáte nejnovější vydání.

---